

4218-W3

Perma-Wrap™

CONTENTS: 30 foot roll: 1/8" x 2" (3mmx50mmx9.1m)

DIRECTIONS FOR USE:

Apply Perma-Wrap™ Foam Insulation Tape by removing release paper as the tape is spirally wrapped around the piping or fittings. Press firmly in place. Avoid stretching.

Pressure-sensitive adhesive adheres firmly and forms a long-lasting bond with metal surfaces.

For a faster and more efficient job, tape should be spiral-wrapped to obtain a 50% overlap. Additional layers build up insulation to required thickness.

To insulate valves, tees, and other fittings, cut small pieces of tape and press into place until all metal is covered.

Overwrap with longer lengths for a durable and efficient job.

COVERAGE:

This table shows the approximate amount of piping per lineal feet that can be covered with one 30-foot roll of insulation tape.

COPPER TUBING SIZE

	A	B	C
3/8" OD	15 1/4	8 1/2	5 1/2
1/2" OD	12 3/4	7 1/4	4 3/4
5/8" OD	11	6 1/2	4
3/4" OD	9 1/2	5 3/4	3 3/4
7/8" OD	8 1/2	5	3 1/2
1" OD	7 1/2	4 1/2	3 1/4
1 1/8" OD	7	4 1/4	3
1 3/8" OD	6	3 1/2	2 1/2
1 5/8" OD	5	3 1/4	2 1/4
2 1/8" OD	4	2 1/2	1 3/4

- A. 50% overlap wrapping
- B. 50% overlap plus single-layer wrapping
- C. 50% overlap plus 50% overlap wrapping

IRON PIPE SIZE

	A	B	C
1/4" IPS	12	7	4 1/2
3/8" IPS	10 1/4	6	4
1/2" IPS	8 3/4	5 1/4	3 1/2
3/4" IPS	7 1/4	4 1/2	3
1" IPS	6	3 3/4	2 1/2
1 1/4" IPS	5	3	2 1/4
1 1/2" IPS	4 1/2	2 3/4	2
2" IPS	3 1/2	2 1/4	1 3/4

THICKNESS TO CONTROL PIPE SWEAT

Air Temp and Relative Humidity	Pipe Temperature	
	50°F (10°C)	35°F (0°C)
80°F & 50% RH	50% Overlap	50% Overlap
80°F & 70% RH	50% Overlap plus Single Layer	50% Overlap plus 50% Overlap

Recommended Service Temperature: Low of -20°F and high continuous to 160°F, high intermittent to 200°F.



Nu-Calgon
2611 Schuetz Road
St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com
(618) Calgon is a licensed trade name.

4218-W3


Perma-Wrap™
CONTENTS: 30 foot roll: 1/8" x 2" (3mmx50mmx9.1m)

4218-W3



Perma-Wrap™

PREMIUM FOAM INSULATION TAPE



Closed Cell Construction

Self Adhesive

Stops Sweating and Condensation

Use on Iron Pipe, Copper Tubing, Tees, Valves & Fittings

30 foot roll: 1/8" x 2" (3mmx50mmx9.1m)

4218-W3

Perma-Wrap™
CONTENTS: 30 foot roll: 1/8" x 2" (3mmx50mmx9.1m)

4218-W3

Perma-Wrap™

CONTENTS: 30 foot roll: 1/8" x 2" (3mmx50mmx9.1m)