

# BULLET<sup>®</sup>X Vacuum Pump



# YELLOW JACKET<sup>®</sup>



**The Quality You Have Come to Expect From a YELLOW JACKET<sup>®</sup> Vacuum Pump at an Affordable Price.**


| DOMESTIC                    | MODEL 93600   |
|-----------------------------|---|
| Free air displacement       | 7.0 cfm   |
| Number of stages            | 2-stage rotary vane                                     |
| Field blankoff              | 25 microns  |
| Intake                      | 1/4" x 3/8" x 3/8"                                      |
| Motor                       | 1/2 hp - 1725 rpm                                       |
| Thermal overload protection | Yes   |
| Voltage (single phase)      | 115V/60 Hz  |
| Power cord                  | 6' - motor mounted switch - U.S. plug                   |
| Oil capacity                | 28 oz. (0.828 L)  |
| Dimensions                  | 17.5" L x 6" W x 12" H<br>(44.5 cm x 15.2 cm x 30.5 cm) |
| Net weight                  | 31.7 lbs. (14.4 kg)                                     |
| EXPORT                      | EU/UK 93610; AU/NZ 93620                                |
| Detachable ICE cord type    | EU/UK                      AU/NZ                        |
| Free air displacement       | 200/165 L/M   |
| Motor                       | 1/2 hp - 1725/1425 rpm                                  |
| Dual voltage (single phase) | 115/230V/50-60 Hz                                       |
| Dimensions                  | 18" L x 6" W x 12" H<br>(45.7 cm x 15.2 cm x 30.5 cm)   |
| Net weight                  | 34.5 lbs. (15.7 kg)                                     |

## YELLOW JACKET<sup>®</sup> BULLET<sup>®</sup>X Vacuum Pump Capabilities Make it the Best Vacuum Pump for the Money.

Our newest generation adds characteristics that makes evacuating a system easier for years to come. The BULLET<sup>®</sup>X is available in 7 cfm to handle most residential and commercial applications. Pulling down to less than 25 microns, BULLET<sup>®</sup>X protects the system from contaminants and non-condensable gases, which can damage components, reduce efficiency and cause system failure.

The BULLET<sup>®</sup>X is a highly efficient, two-stage rotary vane, oil sealed pump that is rated to better than 25 microns. This upgraded BULLET<sup>®</sup>X design combines some of the same great features and benefits with enhancements to improve ergonomics and performance.

### Features and Benefits

- Internal intake check valve to help prevent oil backup into the system during a power failure
- Intake filter screen keeps damaging particles from entering into the pump
- Heavy duty rotors and bearings
- Wide-mouth oil reservoir port for easier and cleaner filling. Doubles as a pump exhaust – threaded to attach a garden hose for exhausting to a remote location
- Large brass oil drain for easy access to fast oil changes
- Downward angled oil sump to remove contaminants usually trapped in other sump designs
- Heavy duty steel handle
- Two-year warranty
- Made in USA 

### Enhancements

- Integrated cooling fins to cool pump and increase performance
- Oil suck-back valve improvement
- Elongated oil sight glass – easier to see oil level